

KW270

SPECIFICATIONS



Processor	■ Freescale iMX27L (ARM9 Core)
Operating System	■ Microsoft Windows® CE 6.0
Storage	■ 128M Fixed NAND Flash "Boot" ■ 256M Removable SDIO "Store"
Memory	■ 256 MB - Fixed on board
Networking	■ On Board 10/100 Ethernet ■ Optional 802.11 Wireless with integrate antennas
Display/Resolution	■ 5.7" Color TFT QVGA
Keyboard	■ 90 Key Membrane Keypad - Fully programmable
Power Supply	■ External, 65W Power Brick with Universal Input
Magnetic Card Reader	■ Modular Integrated 3 Track MSR
Cash Drawer Ports	■ 2 – MICROS 12/24V Ports
Serial Ports	■ 6 Total • 1 Powered DB9 RS232 Serial • 2 RJ45 MICROS IDN/RS232 Serial • 1 RJ45 RS232 Serial • 1 Internal RJ45 Reserved for MSR • 1 Internal "SPI" Interface Reserved
Integrated Customer Display	■ Integrated 2x20 Transflective LCD
USB Ports	■ 5 Total • 2 on Main I/O Panel • 2 on Rear I/O Panel • 1 Internal USB "On The Go" Header
Pole Display Ports	■ Support MICROS Pole Display
Additional I/O Ports	■ 2 SDIO Sockets • 1 – Reserved for "Store" memory card • 1 – Used for Optional Wireless Card
Power Connections	■ 1 – 9V Power Output ■ 1 – 12V Power Output
Operating Temp	■ -10 ⁰ C to 60 ⁰ C (14 ⁰ F to 140 ⁰ F)



FEATURING
Athena
BY ODYSSEY
SOFTWARE

